

Zimmer
MedizinSysteme



Cryo

Disamed

Zimmer


Evaluation of Different Temperatures in Cold Air Cooling With Pulsed-Dye Laser

Stefan Hammes and Christian Raulin, MD* Laserklinik Karlsruhe, Karlsruhe, Germany

Table 1
Treatment Results

Mean Values
Scales 0-3
(0 = no, 1 = Little,
2 = Medium, 3 = High)

■ No cooling
■ 20°C skin
■ 17°C skin



Background and Objectives

Cold air cooling is widely used in dermatological laser therapy. We investigated the influence of cold air cooling at different skin temperatures on therapeutic outcome and side effects of pulsed dye laser treatment of facial telangiectasia.

Study Design / Materials and Methods

From September 2002 to February 2003, 17 patients with previously untreated facial telangiectasia underwent a single treatment session with flash-lamp pulsed dye laser (3.5 J / cm², 585 nm, 0.45 milliseconds pulse length, 10 mm beam diameter, Cynosure 1 V). The treatment area was divided into three sub-areas: no cooling, cold air cooling to 20°C and to 17°C skin temperature. The skin temperature was monitored by a prototype infrared sensor system which controlled the temperature of the cold air stream (Cryo 5). In a prospective study, we collected data on purpura, pain, clearance, and patient satisfaction on numerical analog scales (NAS) from 0 (meaning »no«) to 3 (meaning »high«).

Results

Without cooling, purpura (2.53), pain (2.41), and clearance (2.35) were rated medium to high. Cooling to 20°C reduced purpura (1.12) and pain (1.06), whereas the clearance (2.12) was only slightly affected. Cooling to 17°C reduced purpura (0.88) and pain (0.76) even more, the clearance (2.06) was lowered marginally. Most patients preferred cooling to 20°C skin temperature.

Conclusion

In dermatological laser therapy of facial telangiectasia, the use of cold air cooling can significantly reduce side effects and increase patient satisfaction while only slightly affecting clearance. Cooling to 20°C skin temperature proved to be a well-balanced middle course. For the practical use of cold air cooling, we thus recommend cooling to a level which the patient can tolerate without problems and to try to increase the energy densities.

Cryo



The skin cooling system designed for superficial laser skin procedures.

The Cryo 6 Cold Air Device is intended to minimize pain and thermal injury during laser and dermatological treatments and for temporary topical anesthetic relief for injections.

Unlike other cooling methods, such as contact cooling, cryogen spray or ice packs, the Cryo 6 can cool the epidermis before, during and after the laser energy has been applied, without interfering with the laser beam.

Easy to operate

A large display clearly indicates all treatment parameters. Cryo 6 features a tactile glass keyboard, which permits the selection of 6 preset programs.

Select a program. Press Start. That's it!



An optional articulating arm facilitates hand free operation.

The light weight application hose can be connected to selected laser hand-pieces. The user can easily regulate the air flow as needed.

-30°C Cold Air

Increased Patient Comfort
Hand-free Operation
No Consumables



User Defined Programs

3 supplementary storage possibilities are available for user defined programs.

Storage possibility is available for the user's favorite program. This program appears when the Cryo 6 is turned on and at the conclusion of each treatment.

Additionally, the user can choose 2 sequences to be stored as a program for easy selection.

Individual, Favorite and Sequence Program Storage – 3 user-oriented features providing utmost treatment efficiency and state-of-the-art precision.



Easy Maintenance

A monitoring system measures the defrosted water level and a defrosting feature provides smooth-running daily operation. The air filter is easy to access, just vacuum when dirty.

Economic

Room air is filtered and cooled down to -30°C by closed cooling circuit.

- Cost efficient: no consumable or additional costs
- Powerful: full day operation with no downtime
- Practical: a custom-designed glass shelf just where you need it – for a laser, smoke evacuator or accessories.

Technical Data

Power supply	230 V / 50 Hz 230 V / 60 Hz 115 V / 60 Hz
Power input max.	1 KW
Stand-by function	260 W / h
Protection according to IEC 601-1	Class I, Type B
MDD / MPG	Class IIa
Treatment tube length	180 cm
Housing dimensions	H 645 mm / W 390 mm / L 680 mm
Weight	60 kg
Therapy air flow	9 levels, max. 1000 l / min

6 programs combining air flow and treatment time
3 user defined programs
1 favorite user defined program

Set up Menu
Service Menu

Options



Articulating arm



Standard treatment hose



Wheel with brake

Disamed

DISTRIBUIDORA ANDALUZA DE MEDICINA, S.L.

Jaime Balmes, 6- 41007 Sevilla
Tfnos.: 902889103 / 954574032
Fax.: 954584979
info@disamed.com

Zimmer Elektromedizin GmbH
Junkersstraße 9
D-89231 Neu-Ulm
Tel. +49. (0)7 31. 97 61-291
Fax +49. (0)7 31. 97 61-299
export@zimmer.de
www.zimmer.de

Zimmer
MedizinSysteme